

With "Great Solar", The Sun Is Yours...

PURE PRECISOU LIGHT PRO



BCT-OPP2.0-C

Patent number:ZL2021 3 0197569.2

0



: 3

曲 Light energy charging 🚦 Always bright on rainy days 🚦 Wide lighting range 🏅 Clean Energy

5

Product Parameters

*Battery may be stored up to 3 months then a freshening charge is required.

Solar panel Observed Solar panel 105W(Moor) Panel size 105W(Moor) Battery 64X) Light power 3.2V/90(±5)Ah LiFePO4 Battery Light power 5880 Im (Common 56W LED) Lighting time 6+X/Intelligent power control, and can use remote control to adjust brightness and working mode. Installation height 6+X/Intelligent power control, and can use remote control to adjust brightness and working mode. Installation distance 6+X/Intelligent power control, and can use remote control to adjust brightness and working mode. Installation distance 100000 hours Installation distance 100000 hours Installation diameter 6 Product Size 292×657×137mm Carton size 315×685×155mm (1 pcs/carton) Solar panel carton size 755×695×140mm (4Pcs/carton) CRI Calcon temperature Product Size 200000 hours CRI 6 Product Size 755×695×140mm (4Pcs/carton) Color temperature 100000 hours IP rating 6 IP rating 6	Product name	56W Pure Precisou Light Pro
Panel sizeImage: State of the st	Model	BCT-OPP2.0-C
Battery3.2V/90(±5)Ah LiFePO4 BatteryLight power3.2V/90(±5)Ah LiFePO4 BatteryLight power6+X/Intelligent power control, and can use remote control to adjust brightness and working mode.Installation height6+X/Intelligent power control, and can use remote control to adjust brightness and working mode.Installation height6+X/Intelligent power control, and can use remote control to adjust brightness and working mode.Installation distance6+X/Intelligent power control, and can use remote control to adjust brightness and working mode.Installation distance6+X/Intelligent power control, and can use remote control to adjust brightness and working mode.Installation distance6+X/Intelligent power control, and can use remote control to adjust brightness and working mode.Installation distance6+X/Intelligent power control, and can use remote control to adjust brightness and working mode.Installation distance6+X/Intelligent power control, and can use remote control to adjust brightness and working mode.Installation distance6+X/Intelligent power control, and can use remote control to adjust brightness and working mode.Installation distance6+X/Intelligent power control, and can use remote control to adjust brightness.Installation distance6+X/Intelligent power control, and can use remote control to adjust brightness.Installation distance6+X/Intelligent power control, and can use remote control to adjust brightness.Installation distance6+X/Intelligent power control, and can use remote control to adjust brightness.Solar panel carton size6Color temperature6Installation d	Solar panel	105W(Mono)
Light powerStant in the intervention of t	Panel size	780×680×30×25 mm
Lighting time6+X/Intelligent power control, and can use remote control to adjust brightness and working mode.Installation height6+X/Intelligent power control, and can use remote control to adjust brightness and working mode.Installation height8-10mInstallation distance35-40mGross weight13.87kgLamp life100000 hoursInstallation diameter6+X/Intelligent power control, and can use remote control to adjust brightness and working mode.Product Size100000 hoursCarton size922×657×137mmSolar panel carton size922×657×137mmReam angle100000 hoursCRI100000 hoursIP rating100000 hoursIP rating100000 hoursIV level100000 hoursOperating temperature40°C~70°COperating temperature100000 hoursIV level100000 hours	Battery	3.2V/90(土5)Ah LiFePO4 Battery
Installation height8-00mInstallation distance35-40mGross weight35-40mGross weight35-40mLamp life10000 hoursInstallation diameter460(±3) mmProduct Size292×657×137mmCarton size315×685×155mm(1 pcs/carton)Solar panel carton size795×695×140m (4 Pcs/carton)Beam anglebat wing 150*70*CRIColor temperatureIP rating31IN Level10000 hoursOperating temperature340°C 70°COperating temperature40°C 70°C<	Light power	5800 lm (Common 56W LED)
Installation distance35-40mGross weight13.87kgLamp life100000 hoursInstallation diameter60(±3) mmProduct Size292×657×137mmCarton size292×657×137mmSolar panel carton size315×685×155mm(1 pcs/carton)Beam anglebat wing 150*00*CRIColor temperatureIP rating10000 hoursIN LevelColor temperatureOperating temperature40°C-70°C	Lighting time	6+X/Intelligent power control, and can use remote control to adjust brightness and working mode.
Gross weight Iaamp life Iaamp	Installation height	8-10m
Lamp life10000 hoursInstallation diameter10000 hoursProduct Size\$	Installation distance	35-40m
Installation diameterφ60(±3) mmProduct Size292×657×137 mmCarton size315×685×155mm (1 pcs/carton)Solar panel carton size795×695×140mm (4 Pcs/carton)Beam anglebat wing 150*70°CRIColor temperatureIP rating6100 Color temperatureIK levelColor temperatureOperating temperature-40°C-70°C	Gross weight	13.87kg
Product Size292×657×137mmCarton size292×657×137mmSolar panel carton size315×685×155mm (1 pcs/carton)Solar panel carton size795×695×140mm (4 Pcs/carton)Beam anglebat wing 150*70°CRIColor temperatureIP rating6500K,4000KIK levelIK08Operating temperature-40°c-70°C	Lamp life	100000 hours
Carton size315×685×155mm (1 pcs/carton)Solar panel carton size795×695×140mm (4 Pcs/carton)Beam anglebat wing 150*70°CRIColor temperatureIP rating6500K,4000KIK levelIK 08Operating temperature-40°C~70°C	Installation diameter	φ60(±3) mm
Solar panel carton size 795×695×140mm (4 Pcs/carton) Beam angle bat wing 150*70° CRI Color temperature IP rating 6500K,4000K IK level IK level Operating temperature -40°C-70°C	Product Size	292×657×137mm
Beam angle bat wing 150*70* CRI Description Color temperature G500K,4000K IP rating Image: Color temperature IK level Image: Color temperature Operating temperature -40°C-70°C	Carton size	315×685×155mm (1 pcs/carton)
CRIRa70Color temperature6500K,4000KIP rating1000000000000000000000000000000000000	Solar panel carton size	795×695×140mm (4 Pcs/carton)
Color temperature 6500K,4000K IP rating 1P65 IK level 1K08 Operating temperature -40°C-70°C	Beam angle	bat wing 150*70°
IP rating IP rating IK level IK 08 Operating temperature -40°C~70°C	CRI	Ra70
IK level IK08 Operating temperature -40°C~70°C	Color temperature	6500K,4000K
Operating temperature -40°C~70°C	IP rating	IP65
	IK level	IK08
Working humidity 10%~90%	Operating temperature	-40°C~70°C
	Working humidity	10%~90%

*Note: The above data are typical values. The actual product weight will have an error of about 5%.



Product Size:

Lamp head size chart
Unit:mm



■ 780×680×30×25 mm







Product Details Display



AVERAGE BEAM ANGLE(50%):87.7 DEG

60

30

UNIT:cd _____C0/180,139.5 _____C30/210,114.8

C60/240,51.9 C90/270,44.6

-60

-30





Installation Case

Applicable place:

It is widely used in streets and roads, residential areas, scenic spots, parks, squares, private gardens and other public places.

The product is easy to install, no auxiliary lines required, energy saving and environmental protection, no electricity charge, long service life.

Pure Precisou Light Pro



▲ Myanmar



▲ Shandong,China





▲ Hubei,China

▲ Guangdong,China



▲ Xinjiang,China

▲ Cambodia



▲ Qinghai,China

▲ China

▲ Jiangxi,China